



RUBBER FLOORING FINE RIBBED OIL-RESISTANT - S7-NBR45



INTERIOR	65 +/- 5	Sh A	3	mm	3.4	kg/m²
ENVIRONMENT	HARDNESS		THICKNESS		BASIS WEIGHT	



Bottom side - cloth impression



ADDITIONAL INFORMATION

Temperature range -25/+80 °C, short-term +90 °C.

RESISTANCE

Alkaline resistance	NO
Acid resistance	NO
Oil resistance	HIGHLY RESISTANT
Gasoline resistance	MEDIUM RESISTANT

Rubber roofing for interior surfaces. Durable and easy to maintain with easy handling. In a fine grooved design type S7, oil-resistant in black. In standard thickness 3 mm. It weighs 3.6 kg / m2. Specify in the configurator.

CONFIGURATION OPTIONS

THICKNESS

3 mm	(+/- 0,3 mm)
------	--------------

WIDTH

1200 mm	(+/- 10 mm)
---------	-------------

1000 mm	(+/- 10 mm)
---------	-------------

LENGTH

10 m	(+/- 200 mm)
------	--------------

S7— NBR45

RUBBER FLOORING FINE RIBBED OIL- RESISTANT - S7-NBR45

7645 SWELLING RATES

